



不锈钢扎带

材质：采用不锈钢201，304，316材质，各种长度皆可制作，特殊规格按客户供样制作；

特性：耐酸、耐腐蚀、抗张强度高，使用简单、快捷等优势；

工作温度范围：-60°C-150°C。

Stainless Steel Cable Ties

Material:Stainless steel type:201,304,316,all length are available,special sizes can be customized;

Characteristic:Acid-resisting,anti-corrosion,high tensile strength,simple and easy to use,etc.

Working temperature:-60°C-150°C。

不锈钢喷塑扎带

材质：采用不锈钢201，304，316材质，外喷环氧树脂热固性粉涂料，各种长度皆可制作，接受合理的OEM。

特性：耐酸、耐腐蚀、不易燃烧，抗张强度高，滚珠式结构使得YFCP型扎带具有简单，快捷，不可解开等安装上的优势。

工作温度范围：-40°C-85°C。

Coated Stainless Steel Cable Ties

Material:Stainless steel type:201,304,316,thermosetting epoxy resin coated,all length are available,special sizes can be customized;

Characteristic:Acid-resisting,anti-corrosion,uninflammable,high tensile strength;Unique locking structure(with a small ball)makes it simple and easy to use and can't be unlock.

Operating temperature:-40°C-85°C。

喷塑不锈钢扎带
Coated Stainless Steel Zip Ties



编号 Item NO.		L(长) (mm)	W(宽) (mm)	最大捆扎范围 Max.Bundle Dia.E (mm)	拉力 Min.loop Tensile Strength	
					LBS	KGS
CJS-100	SST-100P	100	4.6	22	135	60
CJS-152	SST-152P	152	4.6	35	135	60
CJS-175	SST-175P	175	4.6	40	135	60
CJS-200	SST-200P	200	4.6	50	135	60
CJS-250	SST-250P	250	4.6	65	135	60
CJS-300	SST-300P	300	4.6	80	135	60
CJS-360	SST-360P	360	4.6	95	135	60
CJS-400	SST-400P	400	4.6	105	135	60
CJS-520	SST-520P	520	4.6	150	135	60
CJS-600	SST-600P	600	4.6	180	135	60
CJS-680	SST-680P	680	4.6	195	135	60
CJS-840	SST-840P	840	4.6	250	135	60
CJS-1050	SST-1050P	1050	4.6	285	135	60
CJS-152	SLT-152P	152	7.9	35	180	80
CJS-175	SLT-175P	175	7.9	40	180	80
CJS-200	SLT-200P	200	7.9	50	180	80
CJS-250	SLT-250P	250	7.9	65	180	80
CJS-300	SLT-300P	300	7.9	80	180	80
CJS-360	SLT-360P	360	7.9	95	180	80
CJS-400	SLT-400P	400	7.9	105	180	80
CJS-520	SLT-520P	520	7.9	150	180	80
CJS-600	SLT-600P	600	7.9	180	180	80
CJS-680	SLT-680P	680	7.9	195	180	80
CJS-840	SLT-840P	840	7.9	250	180	80
CJS-1050	SLT-1050P	1050	7.9	285	180	80
CJS-152	SBT-152P	152	12	35	270	120
CJS-175	SBT-175P	175	12	40	270	120
CJS-200	SBT-200P	200	12	50	270	120
CJS-250	SBT-250P	250	12	65	270	120
CJS-300	SBT-300P	300	12	80	270	120
CJS-360	SBT-360P	360	12	95	270	120
CJS-400	SBT-400P	400	12	105	270	120
CJS-520	SBT-520P	520	12	150	270	120
CJS-600	SBT-600P	600	12	180	270	120
CJS-680	SBT-680P	680	12	195	270	120
CJS-840	SBT-840P	840	12	250	270	120
CJS-1050	SBT-1050P	1050	12	285	270	120