


Quick connector for flexible pipes 波纹管快速接头

赛出品质，创新未来



波纹管快速接头 Quick connector for flexible pipes



- 螺牙规格：公制牙，PG 牙，G(PF/BSP/PS) 牙，NPT 牙（可定制）。
 - 产品材质：采用 UL 认可的尼龙 PA66 制成（防火等级 UL94V-2）制成。
 - 工作温度：-40℃至 100℃。
 - 产品特性：特殊夹紧爪与夹紧圈设计，夹紧波纹管抗拉力强，超快速拔插装卸，提高安装效率。
 - 颜色种类：黑色，灰色，其它颜色可定做。
- 注：特殊规格需要请联系工厂。
- Thread : Metric , PG , G(PF) , NPT thread.
 - Materials : UL approved Nylon PA66 (Flammability UL 94V-2).
 - Working temperature : -40℃ to 100℃ in static state , or instantaneous heat resistance up to 120℃ .
 - Features : Special design of the claws and clamping rings to fix the pipe firmly. Tensile forces resistance. Easy to install.
 - Color : Black(RAL9005) , grey(RAL7035) , other color available upon request.
- Note : Special size and type , please contact us.

产品型号 Model	螺牙规格 teeth	对应浪管 Corresponding to the wave tube	螺纹外径 Thread diameter D1 mm	螺纹长度 Length of thread C mm	内孔 I Inner hole mm	外孔径 B Outside the aperture mm	高度 H	包装 PCS
公制标准								
SC-M12	M12 × 1.5	AD10.0	12	10	7.5	17	33	50
SC-M12	M12 × 1.5	AD13.0	12	10	7.7	20	35.5	
SC-M16	M16 × 1.5	AD13.0	16	10	12	20	35.5	
SC-M16	M16 × 1.5	AD15.8	16	10	12	23	40	
SC-M18	M18 × 1.5	AD13.0	18	10	13.5	20	35.5	
SC-M18	M18 × 1.5	AD15.8	18	12.5	13.5	23	40	
SC-M20	M20 × 1.5	AD13.0	20	10	14	20	35.3	
SC-M20	M20 × 1.5	AD15.8	20	12.5	15.5	23	40.5	
SC-M20	M20 × 1.5	AD18.5	20	12.5	15	26.5	41.3	
SC-M20	M20 × 1.5	AD21.2	20	13.5	15	29.5	45	
SC-M22	M22 × 1.5	AD18.5	22	12.5	16.7	26.5	41.5	
SC-M22	M22 × 1.5	AD21.2	22	13	17.8	29.5	44.5	
SC-M24	M24 × 1.5	AD21.2	24	13	19.5	29.5	45	
SC-M25	M25 × 1.5	AD21.2	25	13.3	20.5	29.5	45	
SC-M25	M25 × 1.5	AD25.0	25	13.7	20	32.2	47	
SC-M25	M25 × 1.5	AD28.5	25	13	20	37	47.5	
SC-M27	M27 × 1.5	AD28.5	27	13	22	37	47.5	
SC-M30	M30 × 1.5	AD28.5	30	13.3	25	37	47.5	
SC-M32	M32 × 1.5	AD28.5	32	13.5	27.2	37	48	
SC-M32	M32 × 1.5	AD34.5	32	15	27.5	44	52	
SC-M36	M36 × 1.5	AD34.5	36	15	30	44	52	
SC-M40	M40 × 1.5	AD34.5	40	15	34.5	44	52	
SC-M40	M40 × 1.5	AD42.5	40	15	34.2	52	54	
SC-M48	M48 × 1.5	AD42.5	48	15	41	51.8	53.5	
SC-M50	M50 × 1.5	AD54.5	50	15.8	42.5	63.4	55	
SC-M60	M60 × 1.5	AD54.5	60	15.5	52.5	64.7	54.2	
SC-M63	M63 × 1.5	AD54.5	63	16	55	65	54	
德制标准								
SC-PG7	PG7	AD10.0	12.5		8	17	33.5	50
SC-PG9	PG9	AD13.0	15	10	11.4	20	35.5	
SC-PG11	PG11	AD15.8	18.6	12.4	14.9	23	40.3	
SC-PG13.5	PG13.5	AD15.8	20.1	10	14.3	23	38	
SC-PG13.5	PG13.5	AD18.5	20.4	12.5	15.6	26.5	41.5	
SC-PG16	PG16	AD21.2	22.5	13	17.9	29.5	44.5	
SC-PG21	PG21	AD28.5	28.3	13	23.5	37	47.5	
SC-PG29	PG29	AD34.5	36.5	15	31	44	52	
SC-PG36	PG36	AD42.5	47	15	40.5	52	54.5	
SC-PG42	PG42	AD54.5	53.9	16	45.8	64.5	54	
SC-PG48	PG48	AD54.5	59.3	16	51.9	65.5	54.5	
英制标准								
SC-G1/2	G1/2	AD21.2	20.95	13	15.2	29.6	45	20
SC-G3/4	G3/4	AD28.5	26.3	13.3	21.5	36.9	47.5	
SC-G1	G1	AD34.5	33	15	26.9	44	51.8	
SC-G1-1/4	G1-1/4	AD42.5	41.6	15	34.5	52	54	