


不锈钢电缆接头 METRIC
Stainless Steel Cable Gland METRIC Thread



概述 Outline

材料: 不锈钢304.316
紧夹件: 尼龙PA(UL File NO: E240925)
密封件: 丁腈橡胶 (NBR)
耐候橡胶 (EPDM)
防护等级: IP68(旋紧部位)
环境温度: -40℃至100℃, 短时至120℃

Material: Stainless steel 304.316
Jinga pieces: Nylon PA (UL File NO: E240925)
Seals: nitrile rubber (NBR)
Weathering rubber (EPDM)
Protection class: IP68 (tightened parts)
Ambient temperature: -40℃ to 100℃, short time to 120℃

技术参数 Technical parameters

螺纹规格 Thread AG	适用电缆 Cable range(mm)	螺纹长度 Thread length(GLmm)	结合长度 Combined length	扳手径 Spanner size(mm)	开孔径 AG mm
M12X1.5	3-6.5	7	19	14	12
M16X1.5	4-8	8	20	19	16
M18X1.5	5-10	8	21	21	18
M20X1.5	6-12	8	22	22	20
M22X1.5	10-14	8	23	24	22
M24X1.5	10-14	9	25	27	24
M25X1.5	10-14	9	25	27	25
M25X1.5	13-18	9	27	30	25
M27X1.5(2)	13-18	9	27	30	27
M28X1.5(2)	13-18	9	27	30	28
M30X1.5(2)	13-18	9	29	32/34	30
M32X1.5(2)	15-22	10	29	36	32
M33X1.5(2)	15-22	10	29	36	33
M36X1.5(2)	18-25	10	31	40	36
M37X1.5(2)	18-25	10	31	40	37
M40X1.5(2)	18-25	11	31	45	40
M42X1.5(2)	22-30	11	35	45	42
M47X1.5(2)	25-33	11	37	50	47
M48X1.5(2)	25-33	11	37	50/52	48
M50X1.5(2)	32-38	12	37	55	50
M54X1.5(2)	32-38	12	38	57	54
M56X1.5(2)	32-38	12	38	60	56
M60X1.5(2)	44-37	13	38	64	60
M63X1.5(2)	37-44	13	38	65/68	63
M64X1.5(2)	37-44	13	38	66/68	64
M72X1.5(2)	42-52	15	42	75	72
M80X1.5(2)	55-56	15	45	85	80
M88X1.5(2)	65-70	15	45	95	88
M100X1.5(2)	78-84	15	45	110	100