

# Watertight Corrugated Tubing Fittings


## 防水浪管快速接头

赛出品质，创新未来



# 防水浪管快速接头

## Watertight Corrugated Tubing Fittings



- 螺牙规格：公制牙，PG 牙，G(PF/BSP/PS) 牙，NPT 牙（可定制）。
  - 产品材质：A.C.F 部分采用 UL 认可的尼龙 PA66 制成（防火等级 UL94V-2）制成（可定制 UL 认可的防火 V-0 防火等级尼龙材料）；B, D 部分采用三元乙丙耐候橡胶制成（可定制耐寒、耐高温橡胶、耐高酸碱、耐化学与抗腐蚀橡胶）。
  - 防护等级：IP68-10。
  - 工作温度：-40℃至 100℃。
  - 产品特性：本款高性能防水尼龙浪管盒接头能完美地抗水压，是一款即使拉扯波纹管也能完全保持气密的产品。产品广泛的应用于移动式的自动化设备之防水、防油与气密的场合。
  - 颜色种类：黑色、灰色、其它颜色可定做。
- 注：特殊规格需要请联系工厂。
- Thread : Metric , PG , G(PF) , NPT thread.
  - Materials : UL approved Nylon PA66 (Flammability UL94V-2 ) for A.C.F part ; Weather-resistant EPDM rubber for B,D parts , (Accept to make super rubber : resist high temperature rubber , resist strong acid/alkali , etc).
  - Protection degree : IP68-10 Bar.
  - Working temperature : -40℃ to 100℃ .
  - Features : The Powerful Watertight Fittings build the best tightening power by avery high and active compression force to resist the ingress of high pressure water jet from any angle which can provide 100% dynamic waterproof and airtight performance over the widest range of corrugated tubings.
  - Color : Black(RAL9005)、grey(RAL7035)、othar color available upon request.
- Note : Special size and type , please contact us.

名称 The name of the	螺牙规格 The teeth specifications	适用 SY 浪管规格 Apply to SY Wave tube specifications	螺纹外径 Thread diameter C1 mm	螺纹长度 Length of thread C2 mm	适用最大口径 Apply to the largest C AL F1	包装 PCS	
长螺纹 long screw grain	M	M12 × 1.5	1/4" 管	12	9	10	
		M16 × 1.5	5/16" 管	16	15	13	
			3/8" 管	16	15	16	
		M20 × 1.5	3/8" 管	20	15	16	
			3/8" 管	20	15	18.3	
		M25 × 1.5	1/2" 管	25	15	22	
	3/4" 管		25	15	26.5		
	PG	M32 × 1.5	1" 管	32	15	34.5	20
			11/4" 管	40	20	43	10
		M50 × 1.5		50	15.3	43	10
			11/2" 管	50	22	49	
		M63 × 1.5	2" 管	63	25	55	10
2" 管			63	25	61		
M90 × 2.0	3" 管	90	25	90	1		
短螺纹 short screw grain	PG	PG7	1/4" 管	12.5	8.5	10	
		PG9	1/4" 管	15.2	9	10	
			5/16" 管	15.2	10	13	
		PG11	5/16" 管	18.6	10	13	
			3/8" 管	18.6	10	16	
		PG13.5	3/8" 管	18.6	10	18.3	
			3/8" 管	20.4	10	16	
		PG16	3/8" 管	20.4	10	18.3	
			3/8" 管	22.5	11	16	
			3/8" 管	22.5	11	18.3	
		PG21	1/2" 管	22.5	10	22	
			1/2" 管	28.3	12.5	22	
			3/4" 管	28.3	12	26.5	
		PG29	3/4" 管	28.3	12	28.5	
			1" 管	37	12	34.5	20
PG36	11/4" 管	47	13	43	10		
PG48	2" 管	59.3	16	55	10		
	2" 管	59.3	16	61	10		